

17" (16.0" VIS) Real Flat monitor



Dare to compare - LightFrame™ 3 for the sharpest and brightest displays ever !

- LightFrame™ 3 - 2 x Normal Brightness
- 17-inch (16.0" VIS) Real Flat color monitor with excellent front of screen performance for use with MACs and PCs
- Autoscan covers horizontal frequencies up to 71 kHz offering a maximum resolution of 1280 x 1024 with flicker free display of 1024 x 768 at up to 89 Hz
- Real Flat High Brightness, High Contrast CRT with high-resolution 0.25 mm dot pitch (0.21 hdp)
- XSD-Xtra Space Design for large screen display in a small footprint: World's shortest 17-inch Real Flat monitor with maximum depth of only 424 mm/16.7"
- Multimedia Base
- TCO '03 certified



Optional Multimedia Base (6G3B11)

All accessories might not be available in all markets. Please check with your local philips representative for availability.



PHILIPS

17" (16.0" VIS) Real Flat monitor



Technical Specifications

CRT panel

- Size (inch/cm) 17"/ 41 cm
- Deflection angle (degrees) 90°
- Dot pitch 0.25 mm
- Horizontal pitch 0.21 mm
- -Tube type Shadow mask, Real Flat, High Brightness, High Contrast, Anti Glare, Anti Static, Anti reflection, Light Transmission 45%
- Phosphor P22
- Recom. display area(mm) 306 x 230 mm
- Recom. display area(inch) 12.0" x 9.0"
- Max. display area(mm) 325 x 244 mm
- Max. display area(inch) 12.8" x 9.6"

Scanning

- Horizontal scanning 30 - 71 kHz
- Vertical scanning 50 - 160 Hz

Video

- Video dot rate 120 MHz
- Input impedance
 - Video 75 Ohm
 - Sync 2.2k Ohm
- Input signal levels 0.7 Vpp
- Sync input signal Separate sync
- Sync polarities Composite sync
- Sync polarities Positive and negative

White color temperature

Chromaticity CIE coordinates

- at 9300 K: x=0.283, y=0.297
- at 6500 K: x=0.313, y=0.329

Resolution & preset modes

- Max. resolution 1280 x 1024
- Recom. resolution 1024 x 768
- 8 user definable modes
- 14 factory preset modes

	H.freq (KHz)	V.freq (Hz)
640 x 350	31.5K	70
640 x 350	37.9K	85
640 x 480	37.9K	72
640 x 480	37.5K	75
640 x 480	50.6K	100
720 x 400	37.9K	85
800 x 600	37.9K	60
800 x 600	48.1K	72
800 x 600	63.9K	100
832 x 624	49.7K	75
1024 x 768	48.4K	60
1024 x 768	56.5K	70
1152 x 864	67.5K	75
1280 x 1024	64.0K	60

Plug and play compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft® Windows® 95/98/Me & 2000/NT/XP compatible
- sRGB

Power management

Complies with EPA Energy Star and NUTEK specifications

- Operation 68 W (typical)
- Off mode/Deep Sleep < 1 W

Low-emission characteristics

- Complies with MPR-II and TCO '03 specifications

Monitor controls and functions

- Main 3-button OSD with LightFrame™ Hotkey
Brightness +/- direct access
Contrast +/- direct access
- On Screen Display Language (English, Spanish, French, German, Italian, Chinese, Portuguese, Korean), zoom, horizontal, vertical, pincushion, balanced, trapezoid, parallelogram, color, reset, degauss, moire, serial number, resolution, frequency, sRGB
- LightFrame™ 3 For improving the picture display of multi media content such as photos, videos and games. Will boost brightness and sharpness performance on user selected areas/windows on the screen. With automatic detection of graphical content in Internet Explorer for the web browsing. Can process up to 16 images simultaneously. One-button full screen mode. Advanced user adjustments via Windows control panel. Easy to use control software for Windows 98, Me, XP and 2000. Software in English, French, German, Spanish, Italian, Portuguese, Dutch, Chinese and Korean

Connections and cables

- Connections on monitor body
 - Video 15-pin D-sub
- Cables D-Sub Video cable(fixed), power cord

Regulatory approvals

- TCO '03
- MPR-II Low Emission
- TÜV/GS, TÜV/Ergo
- FCC-B, UL, CSA, DHHS
- SEMKO, Poland-B sign, C-Tick
- CE, BSMI, PSB
- NUTEK, Energy Star

Physical specifications

- Dim. incl. base (WxHxD) 397 x 383 x 424 mm
- Dim. incl. base (WxHxD) 15.6" x 15.1" x 16.7" inch
- Dim. excl. base (WxHxD) 397 x 333 x 424 mm
- Dim. excl. base (WxHxD) 15.6" x 13.1" x 16.7" inch
- Weight 15.5 kg
- Power supply Please refer to rating label
- Temperature (operational) 0°C to 40°C/ 32°F to 104° F
- Temperature (storage) -25°C to 65°C/ -13°F to 149°F
- Relative humidity 5% to 95%
- MTBF > 75,000 H

Other

- Multimedia Base option type: 6G3B11

As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation.

MacOS is a registered trademark of Apple Computer, Inc.

All data subject to change without notice

Release date: January 2004

www.philips.com

